

Notified body No. 1121
Warrington Certification Limited, Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

Certificate of constancy of performance

1121-CPR- AG5117

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

INOX MD7200 & MD8500 Series Lock Range

See Annex A

Intended use: For use on fire/smoke compartmentation doors

Essential characteristics	Performance	Harmonised technical specification
	Mechanical & Fire Test evidence: 196664, 196665 196667 & 347338	
Self closing 5.4.2 Closing force	Grade 8 = 200Kg door mass with 15N maximum closing force.	EN 12209: 2003 / AC 2005
5.1.2 Re-latching force of latch bolt	>2.5N	
Durability of self closing 5.3.1 Durability of latch action	Grade X = 200,000 cycles with 120N side load on latch bolt.	
Ability to maintain the door in the closed position and not contribute to its spread of fire	Grade 1	
Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Certificate of constancy of performance

1121-CPR- AG5117

Produced for

**UNISON HARDWARE INC.
6 Wayne Court,
Sacramento,
CA 95829 USA**

and produced in the manufacturing plant

J/019

This is coded format and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 12209:2003/AC 2005

under system 1 of AVCP are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **22/10/15** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.



Paul Duggan
Certification Manager
Warrington Certification Ltd



Certificate of constancy of performance

1121-CPR- AG5117

Annex A

INOX MD72 Series Locks

Model	Description
MD7210	Mortice Sashlock
MD7220	Mortice Latch
MD7250	Mortice Nightlatch
<p>MD72 Series Lock Range referenced above can be supplied with 40mm, 45mm, 50mm, 55mm, 60mm backset of all models. All models also include square or radius forend / strikes and can be supplied in the following finishes PC, SC, SN, AB, PB, SB, SSS, PSS, PVD</p>	

INOX MD85 Series Locks

Model	Description
MD8510	Mortice Sashlock
MD8520	Mortice Latch
MD8550	Mortice Nightlatch
<p>MD85 Series Lock Range referenced above can be supplied with 40mm, 45mm, 50mm, 55mm, 60mm backset of all models. All models also include square or radius forend / strikes and can be supplied in the following finishes PC, SC, SN, AB, PB, SB, SSS, PSS, PVD</p>	