

Notified body No. 1121
Warrington Certification Limited, Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

Certificate of constancy of performance

1121-CPR- AG5116

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

INOX MB7200mm & MB8500mm Series Lock Range

See Annex A

Intended use: For use on fire/smoke compartmentation doors

Essential characteristics	Performance	Harmonised technical specification
	Mechanical & Fire Test evidence: WIL 329343, 329343 A, 329343 C & 347338	
Self closing 5.4.2 Closing force	Grade 7 = 100Kg door mass with 15N maximum closing force.	EN 12209: 2003 / AC 2005
5.1.2 Re-latching force of latch bolt	>2.5N	
Durability of self closing 5.3.1 Durability of latch action	Grade S = 200,000 cycles with 50N side load on latch bolt.	
Ability to maintain the door in the closed position and not contribute to its spread of fire	Grade 1	
Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Certificate of constancy of performance

1121-CPR- AG5116

Produced for

**UNISON HARDWARE INC.
6 Wayne Court,
Sacramento,
CA 95829 USA**

and produced in the manufacturing plant

J/019

This is coded format and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 12209:2003/AC 2005

under system 1 of AVCP are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **22/10/15** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.



Paul Duggan
Certification Manager
Warrington Certification Ltd



Certificate of constancy of performance
1121-CPR- AG5116

Annex A

INOX MB7200 Series Locks

Model	Description
MB7210	Mortice Sashlock
MB7220	Mortice Latch
MB7250	Mortice Nightlatch

MB72 Series Lock Range referenced above can be supplied with 40mm, 45mm, 50mm, 55mm, 60mm backset of all models.
All models also include square or radius forend / strikes and can be supplied in the following finishes PC, SC, SN, AB, PB, SB, SSS, PSS, PVD

INOX MB8500 Series Locks

Model	Description
MB8510	Mortice Sashlock
MB8520	Mortice Latch
MB8550	Mortice Nightlatch

MB85 Series Lock Range referenced above can be supplied with 40mm, 45mm, 50mm, 55mm, 60mm backset of all models.
All models also include square or radius forend / strikes and can be supplied in the following finishes PC, SC, SN, AB, PB, SB, SSS, PSS, PVD